





CAPASD508-SERIES

cULus E501953



2P Hook



Critical dimension: ∇

Dim.L=Px5.08

Dim.B=(P-1)x5.08

P=Number of poles (02-24)

	Dim B	Dim L
0-30mm	+/- 0,15	+/- 0,20
over 30-60mm	+/- 0,20	+/- 0,25
over 60-90mm	+/- 0,25	+/- 0,30
over 90mm	+/- 0,30	+/- 0,40

Tolerance	
x.	+/- 0,50
x.x	+/- 0,30
x.xx	+/- 0,10
x°	+/- 1°

Units:mm

Technical data

Technical data in accordance with UL/CUL

	Use Group	B	C	D
Nominal voltage (V)	300	-	300	
Nominal current (A)	10	-	10	
Connection capacity(AWG)	26-12	-	26-12	

Technical data in accordance with IEC

Rated insulation voltage at pollution degree 2 (V)	320		
Rated current/conductor cross-section (A/mm ²)	12 / 2,5		
Solid/stranded(mm ²)	0,2-2,5 / 0,2-2,5		
Surge voltage category/pollution degree	III / 3	III / 2	II / 2
Rated insulation voltage(V)	250	320	630
Rated surge voltage(kV)	4	4	4

General data

Stripping length(mm)	9-10
Flange Screw thread	-
Flange Screw tightening torque(Nm)	-
Insulation Withstanding Voltage	AC1600V / 1min
Insulation Resistance	1000M Ω or more at DC500V
Using temperature range	-40°C-115°C

Materials

Insulation material group	PA 66 I UL94 -V0
Wire guard	PhBz, Tin plated
Spring	Stainless steel
Flange Screw	-

Packing information

Poles	Order Number	SPQ
2	CAPASD50802x000	250
3	CAPASD50803x000	160
4	CAPASD50804x000	120
5	CAPASD50805x000	80
6	CAPASD50806x000	80
7	CAPASD50807x000	60
8	CAPASD50808x000	60
9	CAPASD50809x000	50
10	CAPASD50810x000	40
11	CAPASD50811x000	40
12	CAPASD50812x000	40
13	CAPASD50813x000	30
14	CAPASD50814x000	30
15	CAPASD50815x000	25
16	CAPASD50816x000	25
17	CAPASD50817x000	25
18	CAPASD50818x000	25
19	CAPASD50819x000	25
20	CAPASD50820x000	20
21	CAPASD50821x000	20
22	CAPASD50822x000	20
23	CAPASD50823x000	20
24	CAPASD50824x000	20

Ordering code

CAPA SD 508 xx x xxx
① ② ③ ④ ⑤ ⑥

- ① Type
- ② Product style
- ③ Pitch
- ④ Poles (02-24)
- ⑤ Color
- ⑥ Standard 000 or Custom XXX

Color

0 Black	5 Green
1 Brown	6 Blue
2 Red	G Pale grey
3 Orange	8 Dark grey
4 Yellow	9 White

Key Commercial data

Custom tariff number	8536901000
Country of origin	CN (China)

Mating with headers


CAHAAH508 Series



CAHAAV508 Series



CAHABH508 Series



CAHABV508Series



CAHAEH508 Series



CAHAEV508Series

